

Professional connectors

SCART Audio Video

GREAT VOLUME



444

Cable Ø: mm. 11,0
Soldering type

tasker® 444

Professional Audio/Video SCART connector
GREAT VOLUME

- Characteristics:**
Shell: Ergonomic in printed glazed brass Anti-Oxidant
Applicable Cable Diameter: Max. Ø mm. 11,0
Sheath arrester: Threaded nut in printed brass
Clutches: Gold Plated 24 K - 1,5 µ
Insulation: Plastic Steel resistant up to 120°C. and anti-aging
Inner Contacts: Gold Plated 24 K - 1,5 µ Soldering type
Colour: Silver
Packaging: Multiple of n° 10 pieces

HDMI



461

Cable Ø: mm. 7,3
Soldering type

tasker® 461

HDMI connector – Type A

- Characteristics:**
Shell: Ergonomic in plastic printed material
Applicable Cable Diameter: Max. Ø mm. 7,3
Clutches: Metal
Insulation: Plastic material
Inner Contacts: Soldering type
Colour: Black
Packaging: Multiple of 10 pieces

HDMI



460

Cable Ø: mm. 10,0
Soldering type

tasker® 460

HDMI connector – Type A

- Characteristics:**
Shell: Ergonomic in plastic printed material
Applicable Cable Diameter: Max. Ø mm. 10,0
Clutches: Gold Plated 24 K - 1,5 µ
Insulation: Plastic material
Inner Contacts: Printed circuit - Gold Plated 24 K - 0,5 µ - Soldering type
Colour: Silver
Packaging: Multiple of 10 pieces

BNC 50 Ω



SP 56

Cable Ø: mm. 6,0
Soldering type

tasker® SP 56

Professional BNC Connector – Low Capacity

- Characteristics:**
Impedance: 50 Ω
Shell: Ergonomic in Anodized Metal Anti-Oxidant
Applicable Cable Diameter: Min. Ø mm. 5,0
Max. Ø mm. 6,0
Sheath arrester: Inner with serrated jaws
Clutches: Gold Plated 24 K - 1,5 µ
Insulation: Teflon resistant up to 260°C. and anti-aging
Inner Contacts: Gold Plated 24 K - 1,5 µ Soldering type
Packaging: Multiple of n° 10 pieces